



STANDARD
MIL-STD
188-164A

STANDARD
MIL-STD
810

Size:

0.60m

PMAR-60B

High-Speed Mobile Terminal

The PMAR-60B is a rugged, MIL-STD compliant terminal engineered for both military and commercial use in extreme environments. Its advanced antenna feed ensures seamless operation across GEO, MEO, LEO, and HEO orbits, providing a resilient and cost-effective communication.

Superior Precision

Utilizing a proprietary closed-loop beacon processing system, the PMAR-60B delivers near-zero pointing error for maximum link stability. Its 4 axes mount eliminates the keyhole effect, ensuring uninterrupted connectivity and fluid movement even when the satellite is directly overhead or signal conditions are weak.

Operational Efficiency

Downtime is minimized through an innovative gyro-lock mode that enables instantaneous re-connection after obstructions. Designed for longevity, the unit features sealed brushless motors and a balanced inertial system to reduce wear, lowering maintenance needs and power consumption to just a few watts above BUC requirements.

Key Features

- Available in X, Ku and Ka Band
- GEO, MEO, LEO, HEO Compatible
- High-Precision Stabilization
- 4-Axes Tracking
- Integrated Modem Architecture
- Rapid Blockage Recovery Time
- Single-Cable Solution
- Supports OpenAMIP
- Rapid Acquisition
- Optional 4G/ 5G/LTE supported modem for load balancing and bonding solutions
- High Speed Navigation Option (for 30knots and above)



Scan the QR code for more information.

TECHNICAL SPECIFICATIONS / PMAR-60B

GENERAL SPECIFICATIONS

Reflector Diameter
Stabilization Platform
Tracking Mode
Tracking Accuracy
Modem Interface
Modem Support
Power Input

PMAR-60B

0.6m
3-axis (plus Auto Skew)
Carrier Tracking, SNR Direct Tracking
0.2° RMS
Ethernet, OpenAMIP
iDirect, Newtec, Gilat, THISS, Hughes, Comtech
85V~264V AC / DC, 18-36V

RF CHARACTERISTICS

Frequency (GHz) Tx
Frequency (GHz) Rx
Gain (dBi) Tx
Gain (dBi) Rx
EIRP (dBW)
G/T (dB/K)
Polarization
Cross-Pol Isolation

KU-BAND

13.75 - 14.50
10.70 - 12.75
37.0 @ 14.25GHz
35.5 @ 11.75GHz
44.0 (w 6WBUC)
14.5
Linear
> 30dB

MECHANICAL/ POWER SPEC.

Motion Range
Skew Control
Supported Orbit
Sensors
Dimensions (DxH)
Weight

Azimuth

Unlimited
Automatic, with Pre-set Offset Supported
GEO, MEO, LEO, HEO
IMU
83cm x 79cm
52kg

Elevation

-10° ~ 110°

Roll

±30°

ENVIRONMENTAL SPECIFICATIONS

Temperature Range Operational
Temperature Range Survival
Wind Speed Operational
Wind Speed Survival
Protection Grade

PMAR-60B

-20°C ~ 55°C
-55 ~ +70°C
80 kn
110 kn
IP65

Specifications are subject to change.

